



SEA
ELECTRIC

300-85EV

sea-electric.com

SEA MODEL	SEA-DRIVE® POWER-SYSTEM	GVM	WHEEL BASE	AXLE CONFIG	FRONT AXLE WEIGHT (KG)	FRONT AXLE CAPACITY (KG)	REAR AXLE WEIGHT (KG)	REAR AXLE CAPACITY (KG)	TARE WEIGHT (KG)	PAYLOAD (KG)	MAX BODY LENGTH (MM)
SEA 300-85 100-10	SEA-DRIVE® 100-10	6,500	3,430	4X2	1,840	3,100	1,166	6,000	3,006	3,494	4,703
SEA 300-85 100-10	SEA-DRIVE® 100-10	6,500	3,870	4X2	1,842	3,100	1,183	6,000	3,025	3,475	5,407
SEA 300-85 100-15	SEA-DRIVE® 100-15	7,995	3,430	4X2	1,847	3,100	1,215	6,000	3,062	4,933	4,703
SEA 300-85 100-15	SEA-DRIVE® 100-15	7,995	3,870	4X2	1,848	3,100	1,233	6,000	3,081	4,914	5,407
SEA 300-85 100-15	SEA-DRIVE® 100-15	8,500	3,430	4X2	1,847	3,100	1,215	6,000	3,062	5,438	4,703
SEA 300-85 100-15	SEA-DRIVE® 100-15	8,500	3,870	4X2	1,848	3,100	1,233	6,000	3,081	5,419	5,407
SEA 300-85 120-15	SEA-DRIVE® 120-15	7,995	3,870	4X2	2,069	3,100	1,352	6,000	3,421	4,574	5,467
SEA 300-85 120-15	SEA-DRIVE® 120-15	8,500	3,870	4X2	2,069	3,100	1,352	6,000	3,421	5,079	5,467

-  Most **Cost Effective** power system in the world
-  **Lower Maintenance** and **Operating Costs** - no fuel, fewer moving parts
-  **24/7 Roadside Assist** backed by NTI Truck Assist
-  **Zero Emissions** - reduce your carbon footprint
-  **Exceptional Acceleration** and performance
-  Integration with body suppliers - **100% Electric Power** to operate ancillaries
-  Driver comfort, **Health and Safety** - no noise, no fumes, no heat
-  Unique mid-mounted batteries for **Safety and Dynamics**
-  Three-phase AC 22kW on board charger - **Access the Largest Charging Network** in the world
-  **Vehicle-to-grid (V2G)** capability

SEA-DRIVE®

SEA-DRIVE®	CONTINUOUS POWER	MAXIMUM POWER	PEAK SYSTEM EFFICIENCY	MAXIMUM TORQUE	BATTERY CAPACITY	RANGE	CHARGE TIME
SEA-DRIVE® 100-10	59kW	108kW	95.5%	1,000Nm	100kWh	Up to 250km*	Up to 6 hours, 1.4 hours fast charge
SEA-DRIVE® 100-15	80kW	125kW	95.5%	1,500Nm	100kWh	Up to 250km*	Up to 6 hours, 1.4 hours fast charge
SEA-DRIVE® 120-15	80kW	125kW	95%	1,500Nm	138kWh	Up to 300km*	Up to 8 hours, 1.9 hours fast charge

Standard charging equipment for all SEA-Drive® models features a three-phase 32amp onboard charger with 5 pin plug, charging at up to 22kW/h. Optional DC to DC fast-charging is available.

Standard warranty 3 years, 150,000kms. 5 year battery warranty.

24/7 Roadside Assist backed by NTI Truck Assist throughout standard warranty period.

SEA Electric Asia Ltd

A: Empire Tower 1, Level 27, Room 27060 South Sathron Rd
Yannawa, Sathron
Bangkok 10120 Thailand

T: +66 0 2 098 6454
E: apacsales@sea-electric.com

 @seaelectricev  @seaelectricev  @seaelectricev  @seaelectricev

SEA Electric LLC (USA)
LOS ANGELES

SEA Electric Ltd (UK)
LONDON

SEA Electric GmbH (EU)
VIENNA

SEA Electric Asia (Thai)
BANGKOK

SEA Electric Pty Ltd (Aust)
MELBOURNE

SEA Electric Ltd (NZ)
AUCKLAND

sea-electric.com

*Range figures are intended for comparison purposes only and are based on unladen, cab chassis or van test drive conditions. Actual range achieved will depend upon a number of factors including load and body design, road conditions and topography, regenerative braking configuration and utilisation of electrical accessories. SEA Electric Pty Limited ABN 67 603 241 443. The information on this brochure was correct at the time of printing, all specifications are subject to change without notice. The information in this brochure is general in nature. To the extent permitted by law SEA Electric Pty Limited is not liable by any person as a result of reliance on the content of this brochure. Subject to conditions outlined in SEA Electric Service booklet. All SEA Electric warranties are subject to mandatory prescribed terms under AU Consumer law including customer guarantees. Dec21